
PLOT NO. 60/61, PANDOL INDUSTRIAL AREA, VED ROAD, KATARGAM,
SURAT, GUJARAT -395004

TECHNICAL DATA SHEET RP-604

ACID RESISTANT PAINT

PRODUCT DESCRIPTION

ACID RESISTANT PAINT is a dual pack Fusion polymeric resin and polyamine base Paint, having excellent acid alkaline and water resistant, high performance paint which may be applied to the substrates needing resistance to corrosive chemicals in varied climatic condition.

RECOMMENDED USE

ACID RESISTANT PAINT - formulation is specifically developed for various special application. it can be applied on barrage, gates, pipelines, castings, storage tanks, structural works in fertilizers, chemicals resistance etc.

PRODUCT HIGHLIGHT

- * Excellent Corrosion and Abrasion Resistant
- * Its unique product it serves the purpose seven tank processes * Excellent Resistance to Acid, Alkalis and corrosive chemicals.
- * As Polyamin base is good for anticorrosive prevent the base metal

FILM THICKNESS and SPREADING RATE

Film Thickness	70 (+,-) 100 microns per coat.
Theoretical Coverage	80.5 sq ft per lit per coat.
Mixing Ration : 4:1	

PHYSICAL PROPERTIES

Colour	as per customer's requirement It can be from RAL /BIS standards
Appearance	Semi glossy smooth finish.
Flash Point	23°C
Viscosity	80 (+- 10)sec

PERFORMANCE PARAMETERS

*	Scratch Hardness	No Exposure of metal substrate Passes the Test.
*	Conical mandrel	No film cracking or crazing.
*	Adhesion	No Peel-Off.
*	Salt Spray Resistance	Good resistant
*	Thermal Stability	at 200°C no effect on coating Surface.

SURFACE PREPARATION

All surface should be clean, dry and free from rust and all contamination.
the surface should be assessed and treated in accordance. Bare steel cleanliness blast-cleaning, clean by shots blasting.

SURFACE CONDITIONS

- * Relative Humidity max 50% measured in the vicinity of the Substrate.
- * Ventilation good ventilation is required in confined areas to ensure proper drying.

note :- Do not use heated air until solvents have evaporated from the paint film to avoid surface drying and solvent entrapment. During application and Initial drying of the coating, the coating should not be exposed to high humidity as this can result in loss of gloss.

APPLICATION METHOD

Stir the paint thoroughly and add thinner if essential depending upon the application can be applied by spray or dipping.

POT LIFE.

4 hours after mixing the base and hardner.

DRYING TIME.

Drying time are generally related to air circulation, temperature, film thickness, number of coats and will be affected correspondingly. the figure is given in the table are typical with good ventilation or outdoor exposure.

STORAGE

The product must be store in accordance with national regulation. Storage condition are to keep the containers in dry cool well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

HANDLING

Handle with care, stir well before use.

PACKING QUANTITY

20 LIT /200 LIT PACKING

HEALTH AND SAFETY

Please observe the precautionary notices displayed on the container. Use under well ventilated condition. do not breath or inhale mist. Avoid skin contact. Spillage in the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.



Mfg by **RUDRA ENTERPRISE**

Website: www.rudrapaint.com

E Mail:- rudrapaint@yahoo.com

THE FUTURE OF SURFACE PROTECTION

XXXXXXXXXX-----XXXXXXXXXX